




# Fingerprint Time Attendance System

## Specification



### Model

**S-B100 / S-B100B / S-B100C / S-B100CB**

CPU	32bit RISC CPU
Display	3" B/W LCD
Fingerprint Scanner	High Resolution Optical ( > than 600dpi)
False Fingerprint Detection	Embedded
Transaction Record	1,00,000 Impressions
User Record	3000
Authentication Mode	Finger Print/Proximity Card/Password (Proximity Card Optional)
Instruction	Voice Guided
Communication Mode	TCP/IP/ & USB
FAR & FRR	0.0001% & 0.01% max
Speed Mode	IEEE 802.2, Ethernet TCP/IP
Authentication Angle	360°
Data Backup Support	USB
Authentication OSD	Person Name and ID display
Synchronization	Automatic Server to Device Synchronized
Data Transmission	Online or Offline
Lock Control	Supported
Temperature Humidity	-10°C ~ 50°C lower then 90% RH
Source of Power	DC 9V
Power Backup	Battery (Optional)
Certification	CE & FCC

**S-B100** - Biometric

**S-B100B** - Biometric with Battery Backup

**S-B100C** - Biometric with ID Card

**S-B100CB** - Biometric with ID Card & Battery Backup

Fingerprint Time Attendance System